



Design: Christian Hvidt. Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II.

Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Grösse
	8246087863	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	L430 x W175 x H200
	High5 Grau Lens 1 2730lm 4000K	IP66		Anschlussleitung 2x1mm² 6m	
	Ra>70 Nicht dimmbar	IK08			
	23W LED				
	119 lm/W SDCM:3 L80/B10>80.000 Lens 1, Linse				
	8246087931	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	L430 x W175 x H200
	High5 Grau Lens 2 2960lm 4000K	IP66		Anschlussleitung 2x1mm² 6m	
	Ra>70 Nicht dimmbar	IK08			
	23W LED				
	129 lm/W SDCM:3 L90/B10>100.000, L98/B50>50.000 Lens 2,				
Zubehör					
	8249043943 •				L230 x W98 x H230
	Verzinkt Reduzierstück von Ø76 bis Ø60				

• = Lieferzeit auf Anfrage.