



Design: Christian Hvidt. Mast or wall-mounted (600 mm diameter) IP66 LED luminaire. Base and top made of die-cast aluminium, inner diffuser made of PMMA opal and outer optics made of polycarbonate (PC). Grey or black base and top. Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with five-metre connection cable. Prepared for mounting on 60 mm or designer mast. Safety class II.

Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Grösse
	8246090630 Place Schwarz 2410lm 3000K Ra>80 Nicht dimmbar 21W LED 115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,	Klasse II IP66 IK10	Nicht dimmbar	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
	8246088215 Place Grau 2410lm 3000K Ra>80 DYNADIM 21W LED 115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,	Klasse II IP66 IK10	DYNADIM	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
	8246087999 Place Grau 2410lm 3000K Ra>80 Nicht dimmbar 21W LED 115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,	Klasse II IP66 IK10	Nicht dimmbar	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
	8246090614 Place Schwarz 2510lm 4000K Ra>80 DYNADIM 28W LED 90 lm/W SDCM:3 L90/B10>50.000, L70/B10>100.000 Direkt,	Klasse II IP66 IK10	DYNADIM	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
	8246090643 Place Schwarz 2530lm 4000K Ra>80 Nicht dimmbar 21W LED 120 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,	Klasse II IP66 IK10	Nicht dimmbar	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
	8246088228 Place Grau 2530lm 4000K Ra>80 DYNADIM 21W LED 120 lm/W SDCM:3 L90/B10>50.000, L70/B10>100.000 Direkt,	Klasse II IP66 IK10	DYNADIM	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291

Artikel	Schutzklasse	Controller	Montage/Anschluss	Grösse
 8246087407 Place Grau 2530lm 4000K Ra>80 Nicht dimmbar 21W LED 120 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,	Klasse II IP66 IK10	Nicht dimmbar	Mast - top (Ø60mm), Outdoor Anschlussleitung 2x1mm² 6m	Ø600 x H291
Zubehör				
 8249044492 Place Wandarm Schwarz Wandarm				L350 x W175 x H150
 8249043943 • Verzinkt Reduzierstück von Ø76 bis Ø60				L230 x W98 x H230
 8249044489 Place Wandarm Grau Wandarm				L350 x W175 x H150

• = Lieferzeit auf Anfrage.