



Design: Svein Knudsen / Andrew Smith. Attractive, round luminaire with indirect light that can be mounted to both walls and ceilings, both indoors and outdoors. Made of die-cast powdercoated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Efficient and powerful with several light source variants and option of both sensor and wireless control. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK10.

## Produkt- und Umgebungsbilder



| Artikel                                                                           |                                                                         | Schutzklasse    | Controller      | Montage/Anschluss | Grösse      |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------|-----------------|-----------------|-------------------|-------------|
|  | 633877                                                                  | <b>Klasse I</b> | Sensor          | Anbau, Outdoor    | Ø340 x H105 |
|                                                                                   | <b>Piano 2000 Graphit 1650lm 3000K</b>                                  | <b>IP65</b>     |                 | Anschlussklemme   |             |
|                                                                                   | <b>Ra&gt;80 Sensor</b>                                                  | <b>IK10</b>     |                 |                   |             |
|                                                                                   | <b>14W LED</b>                                                          |                 |                 |                   |             |
|                                                                                   | 118 lm/W SDCM:3<br>L70/B50>100.000<br>Beam: 110°, Direkt/Indirekt, Opal |                 |                 |                   |             |
|  | 633876                                                                  | <b>Klasse I</b> | Phasenabschnitt | Anbau, Outdoor    | Ø340 x H105 |
|                                                                                   | <b>Piano 2000 Graphit 1650lm 3000K</b>                                  | <b>IP65</b>     |                 | Anschlussklemme   |             |
|                                                                                   | <b>Ra&gt;80 Phasenabschnitt</b>                                         | <b>IK10</b>     |                 |                   |             |
|                                                                                   | <b>14W LED</b>                                                          |                 |                 |                   |             |
|                                                                                   | 118 lm/W SDCM:3<br>L70/B50>100.000<br>Beam: 110°, Direkt/Indirekt, Opal |                 |                 |                   |             |
|  | 621876                                                                  | <b>Klasse I</b> | Phasenabschnitt | Anbau, Outdoor    | Ø340 x H105 |
|                                                                                   | <b>Piano 2000 Weiss 1680lm 3000K</b>                                    | <b>IP65</b>     |                 | Anschlussklemme   |             |
|                                                                                   | <b>Ra&gt;80 Phasenabschnitt</b>                                         | <b>IK10</b>     |                 |                   |             |
|                                                                                   | <b>14W LED</b>                                                          |                 |                 |                   |             |
|                                                                                   | 120 lm/W SDCM:3<br>L70/B50>100.000<br>Beam: 110°, Direkt/Indirekt, Opal |                 |                 |                   |             |