











StripLine is a flexible LED strip system designed to provide architectural lighting on ceilings and walls, in niches and cabinets, and is suitable for both indoor and outdoor use. StripLine RGBW allows you to create all the colours of the rainbow by mixing red, green and blue (RGB) in different ways. It also features pure white (W). StripLine RGBW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch. The LED strip is encapsulated to an IP54 rating, and is supplied with mounting tape on the rear and connection cables already fully fitted. The LED strip must be fitted in one of the available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. (The diffuser on roll and the Round Diffuser are not compatible with the Slim and Soft profiles). Different driver kits are available, dimmable with phase-cut or push dim. Driver kits come complete with screwless terminal block for looping. The drivers are encapsulated to an IP20 rating. StripLine RGBW can be cut at intervals of 7.1 cm to be tailored to each individual installation. When cutting, silicone should be applied to maintain water protection.

StripLine RGBW



Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Grösse
 391452 StripLine 5m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50.000 Beam: 120°, Direkt,	Klasse III IP54		Anbau, Indoor / Outdoor Kabel 2x2m	L5000 x W12 x H3.2
 391479 StripLine 10m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50.000 Beam: 120°, Direkt,	Klasse III IP54		Anbau, Indoor / Outdoor Kabel 2x2m	L10000 x W12 x H3.2
Treiber				
 820440 SG Weiss Treiber 24V 36W Phasenabschnitt				L200 x W85 x H35
 820441 SG Weiss Treiber 24V 75W Phasenabschnitt				L200 x W85 x H35
 820442 SG Weiss Treiber 24V 150W Phasenabschnitt				L310 x W85 x H35
Zubehör				
 391457 Remote Control Schwarz RF RGBW				L139 x W36 x H11
 391455 Controller Weiss RF RGBW Fernbedienung RF / Push Dim				L175 x W45 x H27
 820483 LEDDim Smart Color Controller Weiss SG Smart/ Fernbedienung RF * / Push Dim				L175 x W45 x H27