

Tysnes 66 Connect Wireless



Tysnes Connect Wireless is a sealed, slim LED luminaire designed for storage rooms, garages, and parking facilities, featuring an integrated Connect Wireless driver for smart, energy-efficient lighting control. The luminaire is used in combination with other SG Connect devices such as sensors or Connect Switch. Lighting control is easily configured via the SG Connect Commissioning App, and devices communicate wirelessly over Zigbee for flexible, scalable control. Tysnes Connect Wireless offers low power consumption, high light output, and long service life. It can be mounted directly on the ceiling using robust steel clips or with wire suspension. Cable entry at both ends and a knockout for rear cabling simplify installation. The series is available in two lengths to suit different needs.

Tysnes 66 Connect Wireless



Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Grösse
 120055 Tysnes 66 Connect 1200 Grau 5530lm 4000K Ra>80 Connect Wireless 32W LED 173 lm/W SDCM:3 L80/B20>100.000, L90>50.000 Beam: 121°, Direkt, Opal	Klasse II IP66 IK10	Connect Wireless	Anbau, Indoor 3-polige Anschlussklemme mit Durchgangsverdrahtung 3×2,5 mm ²	L1200 x W85 x H80
 120056 Tysnes 66 Connect 1500 Grau 5560lm 4000K Ra>80 Connect Wireless 32W LED 174 lm/W SDCM:3 L80/B20>100.000, L90>50.000 Beam: 121°, Direkt, Opal	Klasse II IP66 IK10	Connect Wireless	Anbau, Indoor 3-polige Anschlussklemme mit Durchgangsverdrahtung 3×2,5 mm ²	L1500 x W85 x H80
Zubehör				
 8249044900 Stahlseile 2x5m				L19 x W25 x H150
 8249044913 Montageset für einstellbaren Winkel				L100 x W98 x H95