

Tysnes 66 Pro



Tysnes 66 Pro is a very efficient, robust version in the Tysnes 66 family. With very high light output and long lifetime it is the project winner for storage rooms, garages, and parking facilities. The luminaire is produced from impact-resistant UV stabilized polycarbonate, and the components can withstand vibrations and very low temperatures (-40°C). It can easily be mounted on ceilings with clips or suspended in wires. Sturdy steel clips attached to the luminaire holds the diffuser. It has cable entries in both ends and weakening for cabling from the back. 5-pole (On/Off) or 7-pole (DALI) terminal block with 5 x 2,5 mm² through wiring gives flexibility for larger installations.

Tysnes 66 Pro



Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Grösse
 120053 Tysnes 66 Pro 1500 Grau 9430lm 4000K Ra>80 DALI-2 55W LED 171 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 119°, Direkt, Opal	Klasse I IP66 IK10	DALI-2	Anbau, Indoor Anschlussbox	L1500 x W85 x H80
 120051 Tysnes 66 Pro 1500 Grau 9430lm 4000K Ra>80 Nicht dimmbar 55W LED 171 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 119°, Direkt, Opal	Klasse I IP66 IK10	Nicht dimmbar	Anbau, Indoor Anschlussbox	L1500 x W85 x H80
 120062 Tysnes 66 Pro 1500 Grau 11060lm 6500K Ra>80 Nicht dimmbar 69W LED 160 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 114°, Direkt, Opal	Klasse I IP66 IK10	Nicht dimmbar	Anbau, Indoor 5-polige Anschlussbox mit Durchgangsverdrahtung 5 x 2,5 mm²	L1500 x W85 x H80
Zubehör				
 120063 Tysnes 66 45° Deckenhalterungen				L45 x W43 x H43
 8249044900 Stahlseile 2x5m				L19 x W25 x H150
 8249044913 Montageset für einstellbaren Winkel				L100 x W98 x H95