

CE – Declaration of Conformity

Document: CE-UKCA250203A_DiLED IV
 Product Inspection: PI250122A
 Risk Assessment: RA250113A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

DiLED IV

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

<i>Directive 2014 / 30 / EU</i>	<i>Directive 2014 / 35 / EU</i>	<i>Directive 2009 / 125 / EF</i>
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	(Regs 244/2009, 245/2009, 347/2010)* Ecodesign requirements (ECO) * As applicable and including amendments

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires – emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)

CE declaration date: 2025

Statement of Conformity

issued by SG Armaturen AS


Manufacturer

Lillesand, 03/02-2025
 Place and date of issue

Martin Ettrup

Approval Engineer

Name of authorized person


Signature of authorized person

UKCA – Declaration of Conformity

Document: CE-UKCA250203A_DiLED IV
 Product Inspection: PI250122A
 Risk Assessment: RA250113A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

DiLED IV

Name(s)

To which this declaration relates is in conformity with the following UK-regulations:

<i>UK SI 2016 No. 1091</i>	<i>UK SI 2016 No. 1101</i>	<i>UK SI 2010 No. 2617</i>	<i>UK SI 2012 No. 3032</i>
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires – emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)
UK SI 2021 No. 1095	(Luminaires – The Ecodesign for Energy-Related products and Energy Information)

UKCA declaration date: 2025

Statement of Conformity

issued by SG Armaturen AS


Manufacturer

Lillesand, 03/02-2025
 Place and date of issue

Martin Ettrup

Approval Engineer

Name of authorized person


Signature of authorized person

Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
5703821182959	DiLED IV 595x595 White 2150lm	4000K Ra>80 CD-DA/230V relay	130254
5703821183031	DiLED IV 600x600 White 3780lm	4000K Ra>80 DALI Sensor	130254
5703821182973	DiLED IV 599x599 White 2700lm	4000K Ra>80 CD-SR Sensor	130254
5703821183017	DiLED IV 599x599 White 4280lm RGBW	3000K Ra>90 DALI-2	130254
5703821182966	DiLED IV 595x595 White 4040lm	4000K DALI GoSense	130254
5703821182942	DiLED IV 300x600 White 2500lm	4000K Ra>80 DALI-2	130254
5703821183000	DiLED IV 750x750 White 3780lm	4000K DALI-2	130254
5703821182980	DiLED IV 600x600 White 3600lm	2700-6500K CD-DA6	130254
5703821178464	DiLED IV 599x599 4040lm	4000K Ra>80 DALI-2	130254
5703821178457	DiLED IV 595x595 4040lm	4000K Ra>80 DALI-2	130254
5703821178471	DiLED IV 584x584 4040lm	4000K Ra>80 DALI-2	130254
5703821179041	DiLED IV 584x584 4040lm	4000K Ra>80 On/Off	130254
824609	DiLED Iv 584x584 4430lm	4000K Ra>80 DALI-2	130254
5703821179096	DiLED IV 584x584 4430lm	4000K Ra>80 On/Off	130254
5703821179089	DiLED IV 599x599 4430lm	4000K Ra>80 DALI-2	130254
5703821179058	DiLED IV 595x595 4430lm	4000K Ra>80 On/Off	130254
5703821179065	DiLED IV 595x595 4430lm	4000K Ra>80 DALI-2	130254
5703821179072	DiLED IV 599x599 4430lm	4000K Ra>80 On/Off	130254
5703821178990	DiLED IV 595x595 White 4040lm	4000K Ra>80 On/Off	130254
5703821179027	DiLED IV 599x599 White 4040lm	4000K Ra>80 On/Off	130254
5703821179003	DiLED IV 599x599 Whvite 2240lm	4000K Ra>80 On/Off	130254
5703821178976	DiLED IV 595x595 White 2240lm	4000K Ra>80 On/Off	130254
5703821178983	DiLED IV 595x595 White 2240lm	4000K Ra>80 DALI-2	130254
5703821179102	DiLED IV 584x584 4430lm	4000K Ra>80 DALI-2	130254
5703821179478	DiLED IV 584x584 2240lm	4000K Ra>80 DALI-2	130254
5703821179010	DiLED IV 599x599 White 2240lm	4000K Ra>80 DALI-2	130254
5703821179034	DiLED IV 584x584 White 2240lm	4000K Ra>80 On/Off	130254
5703821181501	DiLED IV 300x1200 White 4000lm	4000K Ra>80 DALI-2	130254

Emergencybox

5703821177276	Emergencybox	On-Off/Trailing edge / EM Self test, Emergency 3h	130254
5703821177344	Emergencybox Driver	DALI / EM Self test, DALI Emergency 3H	130254
5703821177504	Emergencybox Driver	DALI / EM DALI/Self test, Emergency 3 hours	130254