



Luminaire suspended/surface-mounted directly in 3000 or 4000 Kelvin LED. Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 8246089641 EcoLine Office 1200 Blanc 3680lm 3000K Ra>80 DALI-2 / Push Dim 28W LED 131 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	DALI-2 / Push Dim	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63
 8246090504 EcoLine Office 1200 Blanc 4350lm 3000K Ra>80 DALI-2 / Push Dim 30W LED 145 lm/W SDCM:3 L80/B10>50,000 Directe/indirecte 60/40%, Grille double parabole, mat satiné	Classe I IP20	DALI-2 / Push Dim	Suspendu, Indoor Kit de câble avec boucle M13 avec 2 supports 2x2 m Cable 5x0,75mm ² 2,5m white Bornier sans vis	L1200 x W142 x H81
 8246090546 EcoLine Office 1500 Blanc 4510lm 3000K Ra>80 DALI-2 / Push Dim 35W LED 129 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	DALI-2 / Push Dim	Suspendu ou surface, Indoor Bornier sans vis	L1500 x W142 x H63
 8246089557 EcoLine Office 1200 Blanc 2350lm 3000K Ra>80 Non dimmable 18W LED 131 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63
 8246089638 EcoLine Office 1200 Blanc 3680lm 3000K Ra>80 Non dimmable 28W LED 131 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 8246090106  EcoLine Office 1200 Blanc 2350lm 3000K Ra>80 Non dimmable 18W LED 131 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63
 8246090112 EcoLine Office 1200 Blanc 3060lm 3000K Ra>80 Non dimmable 23W LED 133 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63
 8246090533 EcoLine Office 1500 Blanc 4510lm 3000K Ra>80 Non dimmable 35W LED 129 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis	L1500 x W142 x H63
 8246090575 EcoLine Office 1500 Blanc 4920lm 3000K Ra>80 Non dimmable 34W LED 145 lm/W SDCM:3 L80/B10>50,000 Directe/Indirecte 65/35%, Grille double parabole, mat satiné	Classe I IP20	Non dimmable	Suspendu, Indoor Kit de câble avec boucle M13 avec 2 supports 2x2 m Cable 3x0,75mm² 2,5m w/ Schuko white Bornier sans vis	L1500 x W142 x H81
 8246089586  EcoLine Office 1200 Blanc 2450lm 4000K Ra>80 DALI-2 18W LED 136 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	Classe I IP20	DALI-2	Suspendu ou surface, Indoor Bornier sans vis	L1200 x W142 x H63

Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	8246089667	Classe I	DALI-2 / Push Dim	Suspendu ou surface, Indoor	L1200 x W142 x H63
	EcoLine Office 1200 Blanc 3890lm 4000K Ra>80 DALI-2 / Push Dim 28W LED 139 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	IP20		Bornier sans vis	
	8246090562	Classe I	DALI-2 / Push Dim	Suspendu ou surface, Indoor	L1500 x W142 x H63
	EcoLine Office 1500 Blanc 4710lm 4000K Ra>80 DALI-2 / Push Dim 35W LED 135 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	IP20		Bornier sans vis	
	8246089573	Classe I	Non dimmable	Suspendu ou surface, Indoor	L1200 x W142 x H63
	EcoLine Office 1200 Blanc 2450lm 4000K Ra>80 Non dimmable 18W LED 136 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	IP20		Bornier sans vis	
	8246089654	Classe I	Non dimmable	Suspendu ou surface, Indoor	L1200 x W142 x H63
	EcoLine Office 1200 Blanc 3840lm 4000K Ra>80 Non dimmable 28W LED 137 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	IP20		Bornier sans vis	
	8246090559	Classe I	Non dimmable	Suspendu ou surface, Indoor	L1500 x W142 x H63
	EcoLine Office 1500 Blanc 4710lm 4000K Ra>80 Non dimmable 35W LED 135 lm/W SDCM:3 L80/B10>50,000 Directe, Grille double parabole, mat satiné	IP20		Bornier sans vis	
	8246090591	Classe I	Non dimmable	Suspendu, Indoor	L1500 x W142 x H81
	EcoLine Office 1500 Blanc 5140lm 4000K Ra>80 Non dimmable 34W LED 151 lm/W SDCM:3	IP20		Kit de câble avec boucle M13 avec 2 supports 2x2 m Cable 3x0,75mm² 2,5m w/ Schuko white	

Article	L80/B10>50,000	Protection	Convertisseurs	Montage/Connexion	Dimensions
Directe/Indirecte 55/35%	212255	Grille double parabole, mat satiné			L596 x W35 x H17
		T-profil Blanc Rail de suspension 600mm			
	212048	EcoLine Office 1200 Support asymétrique avec kit suspension			L1050 x W135 x H40
	212049	EcoLine Office Kit suspension			L2000
	6049000874	EcoLine Office Kit de montage pour rail de suspension			
	8249042724 •	Ceiling boîte 2x2m Kit suspension			

• = Cet article est produit sur commande, avec un délai de livraison prévu de 3-4 semaines.