



Design: Christian Hvidt. . Light for mounting on mast or wall lamp (680mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast. Electrical safety class II.

Ray 680



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
	8246079376	Classe I	Non dimmable	haut de poteau - (Ø60mm), Outdoor
	Ray 680 D/I LED Gris 2990lm 3000K	IP65	Cable 3x1mm² 5,0m	Ø680 x H703
	Ra>80 Non dimmable	IK10		
	24W LED			
	125 lm/W SDCM:2 L90/B10>100,000 Directe/Indirecte 85/15%, Opale			
Accessoires				
	8249043943			L230 x W98 x H230
	Galvanisé Pièce de réduction de Ø76 à Ø60			
	8249042999			Ø108 x L100
	Ray 680 Design Cone Gris Cône design			

• = Cet article est produit sur commande, avec un délai de livraison prévu de 3-4 semaines.