



Design: Christian Hvidt. . Light for mounting on mast or wall lamp (460 mm or 680 mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast (76 mm on request). Electrical safety class I or II. Ø460.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 8246088008 • Ray D LED Gris 2710lm 3000K Ra>80 Non dimmable 26W LED 104 lm/W SDCM:3 L80/B10>70,000, L90/B50>50,000 Directe,	Classe II IP65 IK10	Non dimmable	haut de poteau - (Ø60mm), Outdoor Cable 2x1mm² 5,0m	Ø460 x H703
 8246087410 • Ray D LED Gris 2830lm 4000K Ra>80 Non dimmable 26W LED 109 lm/W SDCM:3 L80/B10>70,000, L90/B50>50,000 Directe,	Classe II IP65 IK10	Non dimmable	haut de poteau - (Ø60mm), Outdoor Cable 2x1mm² 5,0m	Ø460 x H703
Accessoires				
 8249043943 • Galvanisé Pièce de réduction de Ø76 à Ø60				L230 x W98 x H230
 8249042999 Ray 680 Design Cone Gris				Ø108 x L100

• = Cet article est produit sur commande, avec un délai de livraison prévu de 3-4 semaines.