



Design: Svein Knudsen / Andrew Smith. Attractive, round luminaire that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Many variants with both sensors and wireless control, as well as various lumen packages. IP65 and vandal-resistant rating IK10.

Galerie de produits et d'environnements



Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	644867	Classe I	Capteur	Surface, Indoor / Outdoor	Ø325 x H120
	Canto 2000 Noir 1520lm 3000K	IP65		Bornier sans vis	
	Ra>80 Capteur	IK10			
	14W LED				
	109 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Directe, Opale				
	644866	Classe I	Coupure de phase	Surface, Indoor / Outdoor	Ø325 x H120
	Canto 2000 Noir 1520lm 3000K	IP65		Bornier sans vis	
	Ra>80 Coupure de phase	IK10			
	14W LED				
	109 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Directe, Opale				
	643866	Classe I	Coupure de phase	Surface, Indoor / Outdoor	Ø325 x H120
	Canto 2000 Graphite 1520lm 3000K	IP65		Bornier sans vis	
	Ra>80 Coupure de phase	IK10			
	14W LED				
	109 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Directe, Opale				
	641866	Classe I	Coupure de phase	Surface, Indoor / Outdoor	Ø325 x H120
	Canto 2000 Blanc 1550lm 3000K	IP65		Bornier sans vis	
	Ra>80 Coupure de phase	IK10			
	14W LED				
	111 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Directe, Opale				