



Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light.

## Galerie de produits et d'environnements





| Article                                                                                                                                                                                                                                                  | Protection                                     | Convertisseurs   | Montage/Connexion                   | Dimensions |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|------------------|-------------------------------------|------------|
| <br>181194<br><b>Econ LED Blanc 790lm 3000K Ra&gt;80</b><br><b>Capteur</b><br><b>10W LED</b><br>79 lm/W SDCM:3<br>L70/B10>50,000<br>Beam: 120°, Directe, Opale          | <b>Classe II</b><br><b>IP44</b><br><b>IK10</b> | Capteur          | Surface, Indoor<br>Bornier sans vis | Ø300 x H92 |
| <br>181193<br><b>Econ LED Blanc 790lm 3000K Ra&gt;80</b><br><b>Coupure de phase</b><br><b>10W LED</b><br>79 lm/W SDCM:3<br>L70/B10>50,000<br>Beam: 120°, Directe, Opale | <b>Classe II</b><br><b>IP44</b><br><b>IK10</b> | Coupure de phase | Surface, Indoor<br>Bornier sans vis | Ø300 x H92 |