

Cube DimToWarm



Attractive downlight for indoor or outdoor use under eaves, 30-degree 360-degree stepless tilt. Mounted directly on ceiling or on known ceiling electrical boxes. Well integrated LED chip with DimToWarm 2800K-2000K via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 42-degree beam angle via reflector. Quick connection between luminaire body and ceiling mounting plate. Luminaire body is snapped into place and secured using two concealed internal screws.

Cube DimToWarm



Galerie de produits et d'environnements





Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 906213 Cube DimToWarm Noir DimToWarm 490lm 2000-2800K Ra>95 Coupure de phase 7.3W LED 67 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Reflector	Classe I IP21	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	L132 x W132 x H65
 906233 Cube DimToWarm Noir DimToWarm 980lm 2000-2800K Ra>95 Coupure de phase 14.8W LED 66 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Reflector	Classe I IP21	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	L231 x W132 x H65
 906211 Cube Blanc DimToWarm 550lm 2000-2800K Ra>95 Coupure de phase 7.3W LED 75 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Reflector	Classe I IP21	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	L132 x W132 x H65
 906231 Cube Blanc DimToWarm 1100lm 2000-2800K Ra>95 Coupure de phase 14.8W LED 74 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Reflector	Classe I IP21	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	L231 x W132 x H65