



Attractive, round LED wall/ceiling luminaire for indoor mounting. Made of painted metal. Diffuser made of UV-stabilised opal polycarbonate. Efficient LED board with long service life. Hatch for easy access to connection, and option of both visible and concealed cabling as well as loopable quick clips. Vandal-resistant rating IK10.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212105 Orion Noir 760lm 2700K Ra>80 Coupure de phase 8W LED 95 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø300 x H87
 212100 Orion Blanc 770lm 2700K Ra>80 Coupure de phase 8W LED 96 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø300 x H87
 212139 Orion Blanc 1480lm 2700K Ra>80 Coupure de phase 15W LED 99 lm/W SDCM:3 L70/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø300 x H87
 212111 Orion Blanc 800lm 3000K Ra>80 Capteur 8W LED 100 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Capteur	Surface, Indoor Bornier sans vis	Ø300 x H87
 212134 Orion Blanc 1510lm 3000K Ra>80 Sensor Dim 15W LED 101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Sensor Dim	Surface, Indoor Bornier sans vis	Ø300 x H87
 212110 Orion Blanc 800lm 3000K Ra>80 Coupure de phase 8W LED 100 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø300 x H87

Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	212115	Classe II	Coupure de phase	Surface, Indoor	Ø300 x H87
	Orion Blanc 1510lm 3000K Ra>80	IP20		Bornier sans vis	
	Coupure de phase	IK10			
	15W LED				
	101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale				
	212126	Classe II	Capteur	Surface, Indoor	Ø300 x H87
	Orion Blanc 1380lm 4000K Ra>80	IP20		Bornier sans vis	
	Capteur	IK10			
	19W LED				
	73 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Directe, Opale				
	212135	Classe II	Sensor Dim	Surface, Indoor	Ø300 x H87
	Orion Blanc 1540lm 4000K Ra>80	IP20		Bornier sans vis	
	Sensor Dim	IK10			
	15W LED				
	103 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Directe, Opale				
	212125	Classe II	Coupure de phase	Surface, Indoor	Ø300 x H87
	Orion Blanc 1540lm 4000K Ra>80	IP20		Bornier sans vis	
	Coupure de phase	IK10			
	15W LED				
	103 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Directe, Opale				