






The Sense Basic LED panel is the perfect choice for price sensitive projects, both for new installations and remodelling. It has a lightweight steel housing only 35 mm high and it is based on backlight. Supplied as an 4-pack.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212186 Sense Basic 600x600 Blanc Incl Alimentation 3760lm 3000K Ra>80 DALI-2 / Push Dim 31W LED 121 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II SELV IP20	DALI-2 / Push Dim	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W595 x H36
 212144 Sense Basic 625x625 Blanc Incl Alimentation 4220lm 4000K Ra>80 DALI-2 / Push Dim 35W LED 121 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II SELV IP20 IK06	DALI-2 / Push Dim	Encastré, Indoor Linect 5 pôles / bornier sans vis	L620 x W620 x H36
 212188 Sense Basic 600x600 Blanc Incl Alimentation 4040lm 4000K Ra>80 DALI-2 / Push Dim 31W LED 130 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II SELV IP20	DALI-2 / Push Dim	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W595 x H36
 212143 Sense Basic 625x625 Blanc Incl Alimentation 4220lm 4000K Ra>80 Non dimmable 35W LED 121 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II SELV IP20 IK06	Non dimmable	Encastré, Indoor Bornier sans vis	L620 x W620 x H36
 212187 Sense Basic 600x600 Blanc Incl Alimentation 4040lm 4000K Ra>80 Non dimmable 31W LED 130 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II SELV IP20	Non dimmable	Encastré, Indoor Bornier sans vis	L595 x W595 x H36

Accessoires

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212780 Sense Decor Soft Blanc 600x600				L595 x W595 x H17
 8249044557 625x625 Blanc Plaque de plâtre/Troldtekt Encadrement encastré				L625 x W625 x H55
 8249045006 Sense 600x600 Blanc Plaque de plâtre/Troldtekt Encadrement encastré				L640 x W640 x H40
 9349031702 Sense 625x625 Blanc Unité de surface				L665 x W665 x H72
 8246094429 Boîtier d'éclairage de secours Alim. DALI / EM Self test, DALI Secours 3H				L270 x W75 x H35
 212792 Sense Basic 625x625				L643 x W627 x H85
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Self test, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35