

Sense Opalprism TW 300x1200



The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in Tunable White 2700-6500K LEDDim or DALI Type 8 depending on whichever driver kit is selected (accessory).

Sense Opalprism TW 300x1200



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212316 Sense TW 300x1200 Blanc Opalprism 4000lm 2700-6500K Ra>80 LED SDCM:3 L80/B20>50,000 Beam: 84°, Directe, Opalprism	Classe III IP40 IK10		Encastré, Indoor Quick connector	L1197 x W297 x H44
Alimentation				
 820239 Sense TW Alimentation Blanc 4000lm 38W TW DALI Type 8 38W	Classe II IP20	TW DALI Type 8	Indoor Linect 5 pôles / bornier sans vis	L215 x W70 x H32
 820093 Sense TW Blanc 4000lm 40W TW LEDDim 40W	Classe II IP20	TW LEDDim	Indoor Linect 3 pôles / bornier sans vis	
Accessoires				
 212257 Sense 300x1200 Blanc Unité de surface				L1203 x W303 x H47
 8249044502 300x1200 Blanc Plaque de plâtre/Troldtekt Encadrement encastré				L325 x W1225 x H55
 8246094429 Boîtier d'éclairage de secours Alim. DALI / EM Self test, DALI Secours 3H				L270 x W75 x H35
 212170 Sense 2m Kit suspension				L2000
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Self test, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 8249045019 Sense 300x1200 Plaque de plâtre/Troldtekt Encadrement encastré				L1240 x W340 x H40