

Sense Basic 300x600




The Sense Basic 300x600 LED panel is ideal both for new installations and remodelling projects. It can directly replace 2x14W T5 and 2x18W T8 luminaires. It has a lightweight steel housing and is based on backlight, yet it is only 35 mm height. High quality non-yellowing PMMA micro prismatic front optics. Easy tool-free installation, twist connector between driver and panel and junction box with automatic strain relief for cables or plastic tubing.

Sense Basic 300x600



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212146 Sense Basic 300x600 Blanc 2180lm 3000K Ra>80 Non dimmable 20W LED 109 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II IP20 IK06	Non dimmable	Indoor Linect 3 pôles / bornier sans vis	L595 x W295 x H36 x D36
 212147 Sense Basic 300x600 Blanc 2220lm 4000K Ra>80 Non dimmable 20W LED 111 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism	Classe II IP20 IK06	Non dimmable	Indoor Linect 3 pôles / bornier sans vis	L595 x W295 x H36 x D36
Accessoires				
 8246094429 Boîtier d'éclairage de secours Alim. DALI / EM Self test, DALI Secours 3H				L270 x W75 x H35
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Self test, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35