

Soft IsoSafe DimToWarm



Attractive downlight for indoor and outdoor use. Mounted directly in insulation. Well integrated LED chip with DimToWarm chip, dimmable via phase-dimming or DALI driver. It includes a junction box that provides strain relief for several types of cables, as well as fixation for plastic tubing. Our IsoSafe products can be mounted directly in insulation (IsoSafe).

Soft IsoSafe DimToWarm



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 903223 Soft IsoSafe DimToWarm Noir 470lm 2000-2800K Ra 98 Coupure de phase / Linect 8W LED 59 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Verre transparent	Classe II SELV IP54	Coupure de phase / Linect	Encastré, Indoor / Outdoor Linect 3 pôles / bornier sans vis	Ø94 x H53
 903231 Soft IsoSafe DimToWarm Blanc 550lm 2000-2800K Ra 98 DALI-2 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Verre transparent	Classe II IP54	DALI-2	Encastré, Indoor / Outdoor Linect 5 pôles / bornier sans vis	Ø94 x H53
 903221 Soft IsoSafe DimToWarm Blanc 550lm 2000-2800K Ra 98 Coupure de phase / Linect 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Directe, Verre transparent	Classe II SELV IP54	Coupure de phase / Linect	Encastré, Indoor / Outdoor Linect 3 pôles / bornier sans vis	Ø94 x H53
Accessoires				
 9143 Rehab Ring Noir 133mm for Junistar, Uniled, Soft & Jupiter				Ø133 x L133 x W133 x H4
 9236 Rehab Ring Noir 180mm for Junistar, Uniled, Soft & Jupiter				Ø180 x H45
 9223 Rehab Ring Blanc 133mm for Junistar, Uniled, Soft & Jupiter				Ø133 x L133 x W133 x H4
 9224 Rehab Ring Blanc 180mm for Junistar, Uniled, Soft & Jupiter				Ø180 x H45



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 9227 Rehab Ring Blanc 250mm for Junistar, Uniled, Soft & Jupiter				Ø250 x H45