

Zip Zoom 1-Circuit



1 circuit rail spot for ZIP rail system with replaceable GU10 LED. Dimmable with phase dimmer.

Mounted using ZIP adapter, which is ideal for SG's one-phase ZIP rail system. Perfect colour rendering due to very high RA value. Made of powder-coated aluminium. Adjustable diffuser can change the light scattering, making ZIP Zoom perfect for use as effect lighting.

Zip Zoom 1-Circuit



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 3152 Zip Zoom Noir 270lm 2700K Ra>90 Coupure de phase 6W LED 45 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Directe,	Classe II IP20	Coupure de phase	Surface, Indoor Rail Zip (adaptateur inclus)	L78 x W73 x H128
 3033 Zip Zoom Acier brossé 270lm 2700K Ra>90 Coupure de phase 6W LED 45 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Directe,	Classe II IP20	Coupure de phase	Surface, Indoor Rail Zip (adaptateur inclus)	L78 x W73 x H128
 3032 Zip Zoom Blanc 310lm 2700K Ra>90 Coupure de phase 6W LED 52 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Directe,	Classe II IP20	Coupure de phase	Surface, Indoor Rail Zip (adaptateur inclus)	L78 x W73 x H128
 3517 • Zip Zoom Acier brossé 280lm 3000K Ra>90 Coupure de phase 6W LED 47 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Directe,	Classe II IP20	Coupure de phase	Surface, Indoor Rail Zip (adaptateur inclus)	L78 x W73 x H128
 3516 • Zip Zoom Blanc 320lm 3000K Ra>90 Coupure de phase 6W LED 53 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Directe,	Classe II IP20	Coupure de phase	Surface, Indoor Rail Zip (adaptateur inclus)	L78 x W73 x H128

• = Cet article est produit sur commande, avec un délai de livraison prévu de 3-4 semaines.