

Frame Round



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors and twilight are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Round



Galerie de produits et d'environnements



Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	605053 Frame Round Noir 860lm 3000K Ra>80 Capteur 8W LED 108 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605051 Frame Round Noir 670lm 3000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605052 Frame Round Noir 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Twilight	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605063 Frame Round Graphite 860lm 3000K Ra>80 Capteur 8W LED 108 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605061 Frame Round Graphite 670lm 3000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605062 Frame Round Graphite 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Twilight	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 605043 Frame Round Blanc 960lm 3000K Ra>80 Capteur 8W LED 120 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor	Ø270 x H77
 605041 Frame Round Blanc 670lm 3000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor	Ø270 x H77
 605042 Frame Round Blanc 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Twilight	Surface, Indoor / Outdoor	Ø270 x H77
 605203 Frame Round Noir 670lm 4000K Ra>80 Capteur 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor	Ø270 x H77
 605081  Frame Round Noir 670lm 4000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor	Ø270 x H77
 605059  Frame Round Noir 670lm 4000K Twilight 7W LED 96 lm/W L70/B20>100,000, L80/B20>75.000 Directe,	Classe II IP66 IK10	Twilight	Surface, Indoor / Outdoor	Ø270 x H77

Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	605064 Frame Round Graphite 890lm 4000K Ra>80 Capteur 8W LED 111 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605091 Frame Round Graphite 670lm 4000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605065 Frame Round Blanc 670lm 4000K Ra>80 Capteur 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Capteur	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605071 Frame Round Blanc 670lm 4000K Ra>80 Coupure de phase 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe, Opale	Classe II IP66 IK10	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77
	605079 [•] Frame Round Blanc 670lm 4000K Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Directe,	Classe II IP66 IK10	Twilight	Surface, Indoor / Outdoor Bornier sans vis	Ø270 x H77

[•] = Cet article est produit sur commande, avec un délai de livraison prévu de 3-4 semaines.