

Rax Soft 150 TW





Rax Soft TW is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft TW is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm. Tunable White 2700-6500K LED Dim or DALI Type 8.

Rax Soft 150 TW



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212575 Rax Soft 150 Satin 2700-6500K Ra>80 TW DALI Type 8 28W LED 93 lm/W SDCM:3 L90/B10>100,000 Beam: 68°, Directe, Réflecteur mat satiné	Classe II SELV IP54/IP20 IK08	TW DALI Type 8	Encastré, Indoor Linect 5 pôles / bornier sans vis	Ø166 x H83
 212574 Rax Soft 150 Satin TW LEDDim 2700-6500K Ra>80 TW LEDDim 28W LED 93 lm/W SDCM:3 L90/B10>100,000 Beam: 68°, Directe, Réflecteur mat satiné	Classe II SELV IP54/IP20 IK08	TW LEDDim	Encastré, Indoor Linect 3 pôles / bornier sans vis	Ø166 x H83
Accessoires				
 212617 Rax 150 Noir Rehabring Ø155-200mm				Ø220 x H16
 212621 Rax 150 Noir Verre transparent IP44				Ø168 x H12
 212623 Rax 150 Noir Verre dépoli IP44				Ø168 x H12
 212620 Rax 150 Blanc Verre transparent IP44				Ø168 x H12
 212622 Rax 150 Blanc Verre dépoli IP44				Ø168 x H12
 8249044683 Rax 150 Blanc Rehabring Ø155-200mm				Ø220 x H16
 8249042216 Rax 150 Plaque de montage				L585 x W260 x H15