

Fevik 1000/2000 + 1500/2500



Fevik is a modern LED luminaire with a slim profile and wide light dispersion, for wall mounting. During installation, the light output is selected from a choice of two levels using a dipswitch on the LED module. The luminaire is made of die-cast aluminium, powder-coated white or graphite, with an aluminium reflector and a tempered glass diffuser. Fevik can be mounted as an upward light or a downward light. With the adjustable wall/corner bracket and ArmMount (accessory), Fevik can be used in most lighting situations. The wall/corner bracket can be angled 180° for wall mounting, and 165° for corners. Using ArmMount, Fevik can be installed on horizontal tubes. Fits Ø42–48 mm tubes and provides an invisible transition between luminaire and wall bracket.

Fevik 1000/2000 + 1500/2500



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 623253 Fevik Graphite 1000/2000 3000K Ra>80 Coupure de phase LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
 623260 Fevik Graphite 1500/2500 3000K Ra>80 Coupure de phase LED 100/89lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
 623255 Fevik Graphite 1000/2000 3000K Ra>80 Twilight LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Twilight	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
 623257 Fevik Blanc 1000/2000 3000K Ra>80 Coupure de phase LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
 623254 Fevik Graphite 1000/2000 4000K Ra>80 Coupure de phase LED 106/102lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
 623261 Fevik Graphite 1500/2500 4000K Ra>80 Coupure de phase LED 108/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 623258 Fevik Blanc 1000/2000 4000K Ra>80 Coupure de phase LED 106/102lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Directe, Reflector	Classe II IP65 IK10	Coupure de phase	Surface, Outdoor Bornier sans vis	W223 x H110 x D276
Accessoires				
 623247 Fevik Armmount Graphite				W130 x H130 x D240
 623248 Fevik Graphite Support de Mât				L225 x W105 x H111
 623249 Fevik Graphite Support mural et d'angle				W220 x H100 x D135
 611248 Fevik Asymétrique Blanc Support				L225 x W105 x H111