









StripLine is a flexible LED strip system for architectural lighting effects in ceilings, walls, niches and cabinets, for both indoor and outdoor use. Stripline TW comes in two colour temperature ranges: 2700–6500K for traditional TW with the normal circadian spectrum, of 2000–4000K for normal use in homes, including warm and cosy colour temperatures. TW allows you to regulate both the lighting level and colour temperature independently. It provides a premium light quality with high efficiency and great colour rendering. The LED strip is rated to IP54, has tape on the back for mounting and comes with connection cables already assembled. The LED strip must be fitted in one of the available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. (The diffuser on roll and the Round Diffuser are not compatible with the Slim and Soft profiles). The LEDs are positioned at very brief intervals and deliver an even light. StripLine TW can be cut per 5.5 cm to customise each individual installation. When cutting, silicone should be applied to maintain water protection. StripLine TW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch.

StripLine TW



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 <p>391420</p> <p>StripLine 3,6m Tunable White</p> <p>950lm/m (@4000K) 2000-4000K</p> <p>Ra>90</p> <p>LED</p> <p>SDCM:3</p> <p>L80/B10>50,000</p> <p>Beam: 120°, Directe,</p>	<p>Classe III</p> <p>IP54</p>		<p>Surface, Indoor / Outdoor</p> <p>Câble 2m</p>	L3600 x W12 x H3.2
 <p>391422</p> <p>StripLine 5m Tunable White</p> <p>1650lm/m (@6500K) 2700-6500K</p> <p>Ra>90</p> <p>LED</p> <p>SDCM:3</p> <p>L80/B10>50,000</p> <p>Beam: 120°, Directe,</p>	<p>Classe III</p> <p>IP54</p>		<p>Surface, Indoor / Outdoor</p> <p>Câble 2m</p>	L5000 x W12 x H3.2
Alimentation				
 <p>820440</p> <p>SG Blanc Driver 24V 36W Coupure de phase</p>				L200 x W85 x H35
 <p>820441</p> <p>SG Blanc Driver 24V 75W Coupure de phase</p>				L200 x W85 x H35
 <p>820442</p> <p>SG Blanc Driver 24V 150W Coupure de phase</p>				L310 x W85 x H35
Accessoires				
 <p>820483</p> <p>LEDDim Smart Color Controller Blanc SG Smart/ Télécommande RF * / Push Dim</p>				L175 x W45 x H27