Rax Soft 200 Connect Wireless

A version of Rax Soft 200, which is combined with a wide range of SG Connect Driver Kit Wireless to provide the desired amount of light. The lighting control is easy to configure using the SG Connect Commissioning App, and the luminaire can be used with a wireless sensor or as part of a larger system, along with other SG Connect luminaires with integrated sensors, which can easily be enlarged or reconfigured as needed. The light is turned on and off after a defined period of time, contributing to energy saving. Rax Soft Connect is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.

Rax Soft 200 Connect Wireless

Galerie de produits et d’environnements

Codes-articles

Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	212772 **Rax Soft 200 Satin 3000K Ra>80** **Connect Wireless** **LED** SDCM:2 L90/B10>100,000 Beam: 62°, Directe, Réflecteur mat satiné	**Classe II SELV** **IP44/IP20** **IK08**	Connect Wireless	Encastré, Indoor Quick connector	Ø216 x H93
	212773 **Rax Soft 200 Satin 4000K Ra>80** **Connect Wireless** **LED** SDCM:2 L90/B10>100,000 Beam: 62°, Directe, Réflecteur mat satiné	**Classe II SELV** **IP44/IP20** **IK08**	Connect Wireless	Encastré, Indoor Quick connector	Ø216 x H93
Alimentation					
	820503 **Kit d'Alimentation Wireless 13W** **300mA Connect** **13W** 100,000	**Classe II** **IP20**	Connect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L157 x W45 x H30
	820504 **Kit d'Alimentation Wireless 18W** **500mA Connect** **18W** 100,000	**Classe II** **IP20**	Connect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L157 x W45 x H30
	820506 **Kit d'Alimentation Wireless 26W** **700mA Connect** **26W** 100,000	**Classe II** **IP20**	Connect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L157 x W45 x H30
	820515 **Kit d'Alimentation Wireless 35W** **900mA Connect** **35W** 100,000	**Classe II** **IP20**	Connect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L157 x W45 x H30
Accessoires					

Codes-articles

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
	212618 **Rax 200 Noir Rehabring Ø205-250mm**			Ø270 x H16
	212619 **Rax 200 Noir Rehabring Ø210-280mm**			Ø300 x H16
	212625 **Rax 200 Noir Verre transparent IP44**			Ø218 x H12
	212627 **Rax 200 Noir Verre dépoli IP44**			Ø220 x H12
	212624 **Rax 200 Blanc Verre transparent IP44**			Ø218 x H12
	212626 **Rax 200 Blanc Verre dépoli IP44**			Ø218 x H12
	8249044696 **Rax 200 Blanc Rehabring Ø205-250mm**			Ø270 x H16
	8249038725 **Rax 200 Plaque de montage**			L585 x W260 x H15