

Ecoline D/I



EcoLine D/I is a slim and stylish suspended luminaire that is designed for quick and easy installation. Direct light with three layer optical system for glare-free light, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices, schools and public buildings. Solid luminaire housing made from powder-coated steel. Optional integrated emergency light upon request.

Galerie de produits et d'environnements



Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	212804	Classe I	DALI-2	Suspendu, Indoor	L1235 x W166 x H58
	EcoLine 1200 Blanc D/I 4650lm 3000K Ra>80 DALI-2 32W LED 145 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 5x0,75mm ² 2,5m	
	212806	Classe I	DALI-2	Suspendu, Indoor	L1600 x W166 x H58
	EcoLine 1600 Blanc D/I 5430lm 3000K Ra>80 DALI-2 35W LED 155 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 5x0,75mm ² 2,5m	
	212812	Classe I	Non dimmable	Suspendu, Indoor	L1235 x W166 x H58
	EcoLine 1200 Blanc D/I 4650lm 3000K Ra>80 Non dimmable 32W LED 145 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 3x0,75mm ² 2,5m	
	212814	Classe I	Non dimmable	Suspendu, Indoor	L1600 x W166 x H58
	EcoLine 1600 Blanc D/I 5430lm 3000K Ra>80 Non dimmable 35W LED 155 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 3x0,75mm ² 2,5m	
	212805	Classe I	DALI-2	Suspendu, Indoor	L1235 x W166 x H58
	EcoLine 1200 Blanc D/I 4850lm 4000K Ra>80 DALI-2 32W LED 152 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 5x0,75mm ² 2,5m	
	212807	Classe I	DALI-2	Suspendu, Indoor	L1600 x W166 x H58
	EcoLine 1600 Blanc D/I 5640lm 4000K Ra>80 DALI-2 35W LED 161 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		Kit de fil 2x2 m Cable 5x0,75mm ² 2,5m	

Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	212813	Classe I	Non dimmable	Suspendu, Indoor	L1235 x W166 x H58
	EcoLine 1200 Blanc D/I 4850lm	IP20		Kit de fil 2x2 m	
	4000K Ra>80 Non dimmable			Cable 3x0,75mm ² 2,5m	
	32W LED				
	152 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism				
	212815	Classe I	Non dimmable	Suspendu, Indoor	L1600 x W166 x H58
	EcoLine 1600 Blanc D/I 5640lm	IP20		Kit de fil 2x2 m	
	4000K Ra>80 Non dimmable			Cable 3x0,75mm ² 2,5m	
	35W LED				
	161 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism				