

Sense Basic 2









The Sense Basic LED panel is the perfect choice for price sensitive projects, both for new installations and remodelling. It has a lightweight steel housing only 36 mm high and it is based on backlight. Now available in a single pack, complete with driver. Various dimming options are available with phase-cut or DALI.








Sense Basic 2



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 <p>212795 Sense Basic 625x625 Blanc Incl Alimentation 4340lm 3000K Ra>80 DALI-2 33W LED 132 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism</p>	Classe II SELV IP20 IK06	DALI-2	Encastré, Indoor Bornier sans vis	L620 x W620 x H29
 <p>212214 Sense Basic 600x600 Blanc Incl Alimentation 4320lm 3000K Ra>80 DALI-2 LINECT 33W LED 131 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism</p>	Classe II SELV IP20 IK06	DALI-2 LINECT	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W595 x H36
 <p>212218 Sense Basic 600x600 Blanc Câble et fiche 2m 3070lm 3000K Ra>80 Coupure de phase 23W LED 133 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism</p>	Classe II SELV IP20 IK06	Coupure de phase	Encastré, Indoor Câble 2m cordon et prise incluse	L595 x W595 x H36
 <p>212213 Sense Basic 600x600 Blanc Incl Alimentation 4320lm 3000K Ra>80 Coupure de phase / Linect 33W LED 131 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism</p>	Classe II SELV IP20 IK06	Coupure de phase / Linect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L595 x W595 x H36
 <p>212794 Sense Basic 625x625 Blanc Incl Alimentation 4340lm 3000K Ra>80 Coupure de phase / Linect 33W LED 132 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism</p>	Classe II SELV IP20 IK06	Coupure de phase / Linect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L620 x W620 x H29
 <p>212216 Sense Basic 600x600 Blanc Incl Alimentation 4390lm 4000K Ra>80 DALI-2 LINECT 33W LED</p>	Classe II SELV IP20 IK06	DALI-2 LINECT	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W595 x H36

Article	133 lm/W SDCM:3	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212215 Sense Basic 600x600 Blanc Incl Alimentation 4390lm 4000K Ra>80 Coupure de phase / Linect 33W LED 133 lm/W SDCM:3 L80/B20>100,000 Directe, Opalprism		Classe II SELV IP20 IK06	Coupure de phase / Linect	Encastré, Indoor Linect 3 pôles / bornier sans vis	L595 x W595 x H36
Accessoires					
 212780 Sense Decor Soft Blanc 600x600					L595 x W595 x H17
 820489 Sensor Dim Box Blanc 200VA					L220 x W75 x H34
 8249045006 Sense 600x600 Blanc Plaque de plâtre/Troldtekt Encadrement encastré					L640 x W640 x H40
 212792 Sense Basic 625x625					L643 x W627 x H85
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Self test, Secours 3 heures					L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures					L270 x W75 x H35