



Energy efficient surface-mounted LED luminaire with a slim profile ensuring a modern look. Square and round available in multiple sizes and lumens. Opalprismatic diffuser provides a glare-free light. The luminaire is produced in a matt black or white powder-coated aluminium finish. Dimmable using a DALI or phase control dimmer. We recommend LEDDim 400 and LEDDim Smart. Simple installation with quick connections between fixture and back plate that can be screwed straight onto all known ceiling boxes. Visible cabling also possible. Also supplied with a sensor and/or emergency light.



**Galerie de produits et d'environnements**



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 <p>606219  <b>Disc 360 Noir 2360lm 2700K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      112 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606222  <b>Disc 360 Blanc 2510lm 2700K Ra&gt;80</b>  <b>Sensor Dim</b>  <b>21W LED</b>                      120 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	Sensor Dim	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606216  <b>Disc 360 Blanc 2510lm 2700K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      120 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606228  <b>Disc 360 Noir 2430lm 3000K Ra&gt;80</b>  <b>DALI-2</b>  <b>21W LED</b>                      116 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	DALI-2	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606220  <b>Disc 360 Noir 2430lm 3000K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      116 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606226  <b>Disc 360 Blanc 2610lm 3000K Ra&gt;80</b>  <b>DALI-2</b>  <b>21W LED</b>                      124 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<p><b>Classe II</b>  <b>IP20</b>  <b>IK10</b></p>	DALI-2	Surface, Indoor Bornier sans vis	Ø360 x H57

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 <p>606217  <b>Disc 360 Blanc 2610lm 3000K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      124 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606229  <b>Disc 360 Noir 2600lm 4000K Ra&gt;80</b>  <b>DALI-2</b>  <b>21W LED</b>                      124 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	DALI-2	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606221  <b>Disc 360 Noir 2600lm 4000K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      124 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606227  <b>Disc 360 Blanc 2680lm 4000K Ra&gt;80</b>  <b>DALI-2</b>  <b>21W LED</b>                      128 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	DALI-2	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606224  <b>Disc 360 Blanc 2680lm 4000K Ra&gt;80</b>  <b>Sensor Dim</b>  <b>21W LED</b>                      128 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	Sensor Dim	Surface, Indoor Bornier sans vis	Ø360 x H57
 <p>606218  <b>Disc 360 Blanc 2680lm 4000K Ra&gt;80</b>  <b>Coupure de phase</b>  <b>21W LED</b>                      128 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 85°, Directe, Opalprism</p>	<b>Classe II</b> <b>IP20</b> <b>IK10</b>	Coupure de phase	Surface, Indoor Bornier sans vis	Ø360 x H57

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 606095 <b>Disc/Frosta Noir Suspension Adaptateur</b>				L5000 x W102 x H22
 606094 <b>Disc/Frosta Blanc Suspension Adaptateur</b>				L5000 x W102 x H22