

CE – Declaration of Conformity

Document: CE-UKCA250507A_Sense Round
 Product Inspection: PI250506A
 Risk Assessment: RA250505A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

Sense Round (190, 255, 320, 495)

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

<i>Directive 2014 / 30 / EU</i>	<i>Directive 2014 / 35 / EU</i>	<i>Directive 2009 / 125 / EF</i>
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	(Regs 244/2009, 245/2009, 347/2010)* Ecodesign requirements (ECO) * As applicable and including amendments

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires - emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 60570:2003	(Luminaires - Electrical supply track systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)

CE declaration date: 2025

Statement of Conformity


issued by SG Armaturen AS

Manufacturer

Lillesand, 07/05-2025
 Place and date of issue

Martin Ettrup

Approval Engineer
 Name of authorized person


 Signature of authorized person

UKCA – Declaration of Conformity

Document: CE-UKCA250507A_Sense Round
 Product Inspection: PI250506A
 Risk Assessment: RA250505A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

Sense Round (190, 255, 320, 495)

Name(s)

To which this declaration relates is in conformity with the following UK-regulations:

<i>UK SI 2016 No. 1091</i>	<i>UK SI 2016 No. 1101</i>	<i>UK SI 2010 No. 2617</i>	<i>UK SI 2012 No. 3032</i>
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires - emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 60570:2003	(Luminaires - Electrical supply track systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)
UK SI 2021 No. 1095	(Luminaires – The Ecodesign for Energy-Related products)

UKCA declaration date: 2025

Statement of Conformity

issued by SG Armaturen AS


Manufacturer

Lillesand, 07/05-2025
 Place and date of issue

Martin Ettrup

Approval Engineer

Name of authorized person


Signature of authorized person

Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
7021982122729	Sense White 255 IsoSafe 1430lm	4000K Ra>80 DALI-2/Push Dim	701572
7021982122859	Sense White 320 IsoSafe 1750lm	2700K Ra>80 DALI-2/Push Dim	701572
7021982122811	Sense White 320 IsoSafe 1870lm	3000K Ra>80 Trailing edge dimming	701572
7021982122767	Sense White 255 IsoSafe 1370lm	3000K Ra>80 DALI-2/Push Dim	701572
7021982122804	Sense White 320 IsoSafe 1750lm	2700K Ra>80 Trailing edge dimming	701572
7021982122750	Sense White 255 IsoSafe 1340lm	2700K Ra>80 DALI-2/Push Dim	701572
7021982122866	Sense White 320 IsoSafe 1870lm	3000K Ra>80 DALI-2/Push Dim	701572
7021982122828	Sense White 320 IsoSafe 1950lm	4000K Ra>80 Trailing edge dimming	701572
7021982122873	Sense White 320 IsoSafe 1950lm	4000K Ra>80 DALI-2/Push Dim	701572
7021982122606	Sense White 190 IsoSafe 620lm	2700K Ra>80 Trailing edge dimming	701572
7021982122675	Sense White 190 IsoSafe 660lm	4000K Ra>80 Trailing edge dimming	701572
7021982122910	Sense White 495 3620lm	3000K Ra>80 Trailing edge dimming	701572
7021982122668	Sense White 190 IsoSafe 630lm	3000K Ra>80 DALI-2/Push Dim	701572
7021982122682	Sense White 190 IsoSafe 660lm	4000K Ra>80 DALI-2/Push Dim	701572
7021982122651	Sense White 190 IsoSafe 620lm	2700K Ra>80 DALI-2/Push Dim	701572
7021982122965	Sense White 495 3620lm	3000K Ra>80 DALI-2/Push Dim	701572
7021982122972	Sense White 495 3800lm	4000K Ra>80 DALI-2/Push Dim	701572
7021982122699	Sense White 255 IsoSafe 1430lm	4000K Ra>80 Trailing edge dimming	701572
7021982122613	Sense White 190 IsoSafe 630lm	3000K Ra>80 Trailing edge dimming	701572
7021982122712	Sense White 255 IsoSafe 1370lm	3000K Ra>80 Trailing edge dimming	701572
7021982122927	Sense White 495 3800lm	4000K Ra>80 Trailing edge dimming	701572
7021982122705	Sense White 255 IsoSafe 1340lm	2700K Ra>80 Trailing edge dimming	701572
7021982123115	Sense White 255	3000K	701572
7021982123122	Sense White 255	3000K DALI-2	701572

Accessories

5703821177344	Emergencybox Driver DALI/EM Self-test	DALI Emergency 3H	701572
5703821177276	Emergencybox On-Off/Trailing edge/EM	Self-test Emergency 3H	701572
5703821177504	Emergencybox Driver DALI/EM DALI	Self-test Emergency 3H	701572