



Design: Christian Hvidt. . Light for mounting on mast or wall lamp (680mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast. Electrical safety class II.

Ray 680



Immagini del prodotto e dell'ambiente



Articolo	Protezione	Apparecchiatura di controllo	Montaggio/Collegamento	Dimensioni
 8246079376 Ray 680 D/I LED Grigio 2990lm 3000K Ra>80 Non dimmerabile 24W Lampade fluorescenti compatte 125 lm/W SDCM:2 L90/B10>100.000 Diretto/indiretto 85/15 per cento, Opale	Classe I IP65 IK10	Non dimmerabile	Montante - superiore (Ø60 mm), Outdoor Cavo 3x1mm² 5,0m	Ø680 x H703
Accessori				
 8249043943 • Galvanizzato Presa di transizione da Ø76 a Ø60				L230 x W98 x H230
 8249042999 Ray 680 Cono di design Grigio				Ø108 x L100

• = Questo articolo viene prodotto su ordinazione, con tempi di consegna previsti di 3-4 settimane.