

Econ LED



Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light.

Econ LED



Immagini del prodotto e dell'ambiente



Articolo		Protezione	Apparecchiatura di controllo	Montaggio/Collegamento	Dimensioni
	181194	Classe II	Sensore	Montaggio a superficie, Indoor	Ø300 x H92
	Econ LED Bianco 790lm 3000K	IP44		Morsetto rapido	
	Ra>80 Sensore	IK10			
	10W Lampade fluorescenti compatte				
	79 lm/W SDCM:3 L70/B10>50.000 Beam: 120°, Diretto, Opale				
	181193	Classe II	Taglio di fase	Montaggio a superficie, Indoor	Ø300 x H92
	Econ LED Bianco 790lm 3000K	IP44		Morsetto rapido	
	Ra>80 Taglio di fase	IK10			
	10W Lampade fluorescenti compatte				
	79 lm/W SDCM:3 L70/B10>50.000 Beam: 120°, Diretto, Opale				