

Soft IsoSafe DimToWarm



Attractive downlight for indoor and outdoor use. Mounted directly in insulation. Well integrated LED chip with DimToWarm chip, dimmable via phase-dimming or DALI driver. It includes a junction box that provides strain relief for several types of cables, as well as fixation for plastic tubing. Our IsoSafe products can be mounted directly in insulation (IsoSafe).

Soft IsoSafe DimToWarm



Immagini del prodotto e dell'ambiente



Articolo	Protezione	Apparecchiatura di controllo	Montaggio/Collegamento	Dimensioni
 903223 Soft IsoSafe DimToWarm Nero 470lm 2000-2800K Ra 98 Taglio di fase / Linect 8W Lampade fluorescenti compatte 59 lm/W SDCM:3 L90/B10>50.000 Beam: 42°, Diretto, Vetro trasparente	Classe II SELV IP54	Taglio di fase / Linect	Precipitazioni, Indoor / Outdoor 3 poli Linect / morsetto rapido	Ø94 x H53
 903231 Soft IsoSafe DimToWarm Bianco 550lm 2000-2800K Ra 98 DALI-2 8W Lampade fluorescenti compatte 69 lm/W SDCM:3 L90/B10>50.000 Beam: 42°, Diretto, Vetro trasparente	Classe II IP54	DALI-2	Precipitazioni, Indoor / Outdoor 5 poli Linect / morsetto rapido	Ø94 x H53
 903221 Soft IsoSafe DimToWarm Bianco 550lm 2000-2800K Ra 98 Taglio di fase / Linect 8W Lampade fluorescenti compatte 69 lm/W SDCM:3 L90/B10>50.000 Beam: 42°, Diretto, Vetro trasparente	Classe II SELV IP54	Taglio di fase / Linect	Precipitazioni, Indoor / Outdoor 3 poli Linect / morsetto rapido	Ø94 x H53
Accessori				
 9143 Rehab Ring Nero 133 mm per Junistar, Uniled, Soft e Jupiter				Ø133 x L133 x W133 x H4
 9236 Rehab Ring Nero 180 mm per Junistar, Uniled, Soft e Jupiter				Ø180 x H45
 9223 Rehab Ring Bianco 133 mm per Junistar, Uniled, Soft e Jupiter				Ø133 x L133 x W133 x H4
 9224 Rehab Ring Bianco 180 mm per Junistar, Uniled, Soft e Jupiter				Ø180 x H45



Articolo	Protezione	Apparecchiatura di controllo	Montaggio/Collegamento	Dimensioni
	9227			Ø250 x H45
Rehab Ring Bianco 250 mm per Junistar, Uniled, Soft e Jupiter				