



LEDDim 350 with digital phase cut dimmer ensures stable dimming of the light even without connection N, which is optional. The dimmer automatically adapts to the light sources and ensures that the maximum light level is stable. It is possible to adjust light levels to the light sources by manually setting the minimum and maximum level. Switch the light on/off from two-way wall switch for multiple entrance points in corridors and staircases.

LEDDim 350



Immagini del prodotto e dell'ambiente



Articolo		Protezione	Apparecchiatura di controllo	Montaggio/Collegamento	Dimensioni
	820481 LEDDim Nero 350VA	IP20	Taglio di fase	Precipitazioni, Indoor	L84 x W84 x H42
	820470 LEDDim Bianco 350VA	IP20	Taglio di fase	Precipitazioni, Indoor	L84 x W84 x H42
Accessori					
	820417 LEDDim 350/400/Smart Nero SG Anteriore				L83 x W83 x H29
	820330 LEDDim Grigio			Indoor	L56 x W5 x H56
	820418 LEDDim 350/400/Smart Color argento Adattatore Elko				L55 x W55 x H12
	78500 Tappo a muro Bianco 1X	IP41		Precipitazioni, Indoor	L86 x W86 x H35
	820352 LEDDim 350/400/Smart Bianco Adattatore ABB				L55 x W55 x H10
	820353 LEDDim 350/400/Smart Bianco Adattatore Schneider				L56 x W56 x H12
	820424 LEDDim 350/400/Smart Bianco SG Anteriore				L83 x W83 x H23