


EAN:	7021989239994
SG varenr.:	923999



Wattage:	15W
Systemeffekt (W):	18W
Spænding:	220-240V
Maks. antal armaturer pr. afbryder:	B10: 19, B16: 30, C10: 31, C16: 51

Lyskilde:	LED
Lumen output:	1260lm
Effekt:	70 lm/W
Farvetemperatur:	2700K
Farvegengivelse (CRI):	Ra>90
MacAdams faktor:	SDCM: 2
Levetid:	L90/B10>100.000
Lysfordeling:	Direkte
Optik:	Reflektor
Lysspredning:	40°
UGR:	UGR<22

Type: Bagkantsdæmp

Isolationsklasse: Klasse II SELV
IP Klasse: IP65/IP20

Indeholder lyskilde med energiklasse:	E
Breeam:	Opfylder Hea 01 for flimmerfrit lys

Materiale:	Aluminium
Farve:	Graphit
Afskærmningsmateriale:	Hærdet glas

Montering: Indbygget, Interiør / Udendørs
Tilslutning: Klemmerække

Højde (mm) H:	112
Diameter (mm) D:	114
Cut-out (mm):	83
Lofttykkelse (mm):	110
Afstand til brandbart materiale i stråleretningen:	100mm
Vægt (kg) brutto/netto:	0.906 / 0.9

Forpakningsstørrelse (mm): 114 x 114 x 110

