

Prelude Square Sort 1370lm 2000-4000K Ra>80 Tunable White LEDDim

EAN: 7021981113957
 SG varenr.: 111395



Elektrisk

Systemeffekt (W): 12W
 Spænding: 220-240V
 Frekvens (Hz): 50/60Hz
 Maks. antal armaturer pr. afbryder: B10: 74, B16: 118, C10: 74, C16: 118

Lysteknik

Lyskilde: LED
 Lumen output: 1370lm
 Effekt: 114 lm/W
 Farvetemperatur: 2000-4000K
 Farvegengivelse (CRI): Ra>80
 MacAdams faktor: SDCM: 3
 Levetid: L80/B50>100.000
 Lysfordeling: Direkte
 Optik: Akryl afskærmning

Dimmertype

Type: Tunable White LEDDim

Beskyttelse

Isolationsklasse: Klasse II

Energi og godkendelser

Indeholder lyskilde med energiklasse: C
 Breeam: Opfylder Hea 01 for flimmerfrit lys

Materialer og overflader

Materiale: Aluminium
 Farve: Sort (RAL 9004)
 Afskærmningsmateriale: Akryl (PMMA)

Montering/Tilslutning

Montering: Påbygget, Interiør
 Tilslutning: Klemmerække

Dimensioner

Bredde (mm) W: 519
 Højde (mm) H: 59
 Dybde (D): 62
 Vægt (kg) brutto/netto: 0.963 / 0.963

Forpakning

Forpakkingsstørrelse (mm): 528 x 65 x 65

