

Sense Driver Hvid 3000lm 25W 700mA Bagkantsdæmp

EAN: 7021988204900
 SG varenr.: 820490
 Erstatte: 820080



Elektrisk

Wattage: 25W
 Systemeffekt (W): 25W
 Spænding: 220-240V
 Maks. antal armaturer pr. afbryder: B10: 18, B16: 30, C10: 31, C16: 51

Lysteknik

Levetid: 100.000

Dimmertype

Type: Bagkantsdæmp
 Driver: 700mA

Beskyttelse

Isolationsklasse: Klasse II

Energi og godkendelser

Breeam: Opfylder Hea 01 for flimmerfrit lys

Materialer og overflader

Materiale: Plast
 Farve: Hvid

Montering/Tilslutning

Montering: Indbygget, Interiør
 Kabel: Kabel 2m
 Tilslutning: Inkl. ledning og prop

Dimensioner

Længde (mm) L: 108
 Bredde (mm) W: 53
 Højde (mm) H: 30
 Vægt (kg) brutto/netto: 0.384 / 0.32

Forpakning

Forpakkingsstørrelse (mm): 330 x 100 x 45



Sense Panels & Driver Kits									
	CU	CU/CA	BA	SENSE 3000lm 100000h PHASE DIM (700mA)	SENSE 4000lm 100000h NON DIM (1400mA)	SENSE 5000lm 100000h NON DIM (1400mA)	SENSE 3000lm 100000h DALI	SENSE 4000lm 100000h DALI	SENSE 5000lm 100000h DALI (1400mA)
SENSE OPAL 3-4000lm LED 3000K	80	3	110	2750lm UGR<22 21W/128lm/W	4000lm UGR<22 31.2W/127lm/W	*	2750lm UGR<22 21W/128lm/W	4000lm UGR<22 31.2W/127lm/W	*
SENSE OPAL 3-4000lm LED 4000K	80	3	110	2650lm UGR<22 21W/124lm/W	3900lm UGR<22 31.2W/124lm/W	*	2650lm UGR<22 21W/124lm/W	3900lm UGR<22 31.2W/124lm/W	*
SENSE OPAL 3000lm LED 3000K	80	3	110	2750lm UGR<22 21W/128lm/W	4000lm UGR<22 31.2W/127lm/W	5000lm UGR<22 42W/121lm/W	2750lm UGR<22 21W/128lm/W	4000lm UGR<22 31.2W/127lm/W	5000lm UGR<22 42W/121lm/W
SENSE OPAL 3000lm LED 4000K	80	3	110	2650lm UGR<22 21W/124lm/W	3900lm UGR<22 31.2W/124lm/W	4900lm UGR<19 42W/118lm/W	2650lm UGR<22 21W/124lm/W	3900lm UGR<22 31.2W/124lm/W	4900lm UGR<19 42W/118lm/W
SENSE PRODIM 3-4000lm LED 3000K	80	3	90	2650lm UGR<17 21W/124lm/W	3900lm UGR<17 31.2W/124lm/W	*	2650lm UGR<17 21W/124lm/W	3900lm UGR<17 31.2W/124lm/W	*
SENSE PRODIM 3-4000lm LED 4000K	80	3	90	2550lm UGR<17 21W/118lm/W	3750lm UGR<17 31.2W/118lm/W	4800lm UGR<19 42W/118lm/W	2550lm UGR<17 21W/118lm/W	3750lm UGR<17 31.2W/118lm/W	4800lm UGR<19 42W/118lm/W
SENSE PRODIM 3000lm LED 3000K	80	3	90	2650lm UGR<17 21W/124lm/W	3900lm UGR<17 31.2W/124lm/W	4900lm UGR<19 42W/118lm/W	2650lm UGR<17 21W/124lm/W	3900lm UGR<17 31.2W/124lm/W	4900lm UGR<19 42W/118lm/W
SENSE PRODIM 3000lm LED 4000K	80	3	90	2550lm UGR<17 21W/118lm/W	3750lm UGR<17 31.2W/118lm/W	4800lm UGR<19 42W/118lm/W	2550lm UGR<17 21W/118lm/W	3750lm UGR<17 31.2W/118lm/W	4800lm UGR<19 42W/118lm/W

*None efficiency calculations are incl. driver
Incl. driver: 7.14% loss depending on driver



7 0 2 1 9 8 8 2 0 4 9 0 0