


EAN:	7021983208507
SG varenr.:	320850



System effekt (W):	41W
Spænding:	220-240V
Frekvens (Hz):	50/60Hz
Maks. antal armaturer pr. afbryder:	B10: 32, B16: 50, C10: 50, C16: 85



Lyskilde:	LED
Lumen output:	3620lm
Effekt:	88 lm/W
Farve temperatur:	3000K
Farvegengivelse (Ra):	Ra>90
MacAdams faktor:	SDCM: 2
Levetid:	L90/B10>100.000
Maximum omgivelsestemperatur:	35°C
Levetid ved max. omgivelsestemp.:	L90/B10>50.000
Lysfordeling:	Direkte
Optik:	Reflektor
Lysspredning:	32°
UGR:	UGR<10
Synligt flimmer (PstLM):	0.03
Stroboskopisk flimmer (SVM):	0.01

Type:	On/Off
Driver:	1050mA

Isolationsklasse: Klasse II
IP Klasse: IP20

Indeholder lyskilde med energiklasse:	E
Breeam:	Opfylder Hea 01 for flimmerfrit lys

Materiale:	Aluminium
Afskærmningsmateriale:	Glas

Montering: Påbygget, Indendørs
Tilslutning: ShopLine-skinne (adapter medfølger)

Længde (mm) L:	278
Bredde (mm) W:	234
Højde (mm) H:	92
Vægt (kg) brutto/netto:	1.45 / 1.063

Forpakningsstørrelse (mm): 285 x 225 x 100

