

Circulus Pendant



Pendant suspension on three adjustable wires, wholly uniform light with attractive design, made of powder-coated steel, simple to mount using ceiling electrical box that can be screwed on to all known ceiling outlets/electrical boxes, clips with option of additional looping, current sent from driver to lamp via the adjustable wires so that there are no visible wires, dimmable driver Phase cut-off/DALI, both visible and concealed cabling possible.

Circulus Pendant



Produkt- og miljøbilleder



Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 7021982140051 Circulus Pendel Sort 1420lm 2700K Ra>80 Bagkantsdæmp 15W LED 95 lm/W SDCM:3 L80/B10>50.000, L70/B50>100.000 Beam: 110°, Direkte, Opal	Klasse I IP20	Bagkantsdæmp	Nedhængt, Indoor Klemmerække	Ø360 x H280
 7021982120053 Circulus Pendel Hvid 1420lm 2700K Ra>80 Bagkantsdæmp 15W LED 95 lm/W SDCM:3 L80/B10>50.000, L70/B50>100.000 Beam: 110°, Direkte, Opal	Klasse I IP20	Bagkantsdæmp	Nedhængt, Indoor Klemmerække	Ø360 x H280
 7021982140068 Circulus Pendel Sort 1530lm 3000K Ra>80 Bagkantsdæmp 15W LED 102 lm/W SDCM:3 L80/B10>50.000, L70/B50>100.000 Beam: 110°, Direkte, Opal	Klasse I IP20	Bagkantsdæmp	Nedhængt, Indoor Klemmerække	Ø360 x H280
 7021982120060 Circulus Pendel Hvid 1530lm 3000K Ra>80 Bagkantsdæmp 15W LED 102 lm/W SDCM:3 L80/B10>50.000, L70/B50>100.000 Beam: 110°, Direkte, Opal	Klasse I IP20	Bagkantsdæmp	Nedhængt, Indoor Klemmerække	Ø360 x H280