

Curve



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a down/uplight or as a down or uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

Curve



Produkt- og miljøbilleder



Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 7021986143409 Curve Sort 500lm 2700K Ra>80 Bagkantsdæmp 7W LED 71 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°/110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
 7021986233407 Curve Grafit 500lm 2700K Ra>80 Bagkantsdæmp 7W LED 71 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°/110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
 7021986113402 Curve Hvid 580lm 2700K Ra>80 Bagkantsdæmp 7W LED 83 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°/110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
 7021986143416 Curve Sort 520lm 3000K Ra>80 Bagkantsdæmp 7W LED 74 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°/110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
 7021986233414 Curve Grafit 520lm 3000K Ra>80 Bagkantsdæmp 7W LED 74 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°/110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
 7021986113419 Curve Hvid 600lm 3000K Ra>80 Bagkantsdæmp 7W LED 86 lm/W SDCM:3	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103

Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 Beam: 110°/110°, Direkte/Indirekte, Glas klar 7021986000023 Curve Grafit 530lm 4000K Ra>80 Bagkantsdæmp 7W LED 76 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Beam: 110°, Direkte/Indirekte, Glas klar	Klasse I IP65 IK06	Bagkantsdæmp	Påbygget, Indoor / Outdoor Klemmerække	W320 x H60 x D103
Tilbehør				
 7021986000023 Nummerskilt 320x271mm			Indoor / Outdoor	L320 x W271 x H10