

Sense Basic 300x600





The Sense Basic 300x600 LED panel is ideal both for new installations and remodelling projects. It can directly replace 2x14W T5 and 2x18W T8 luminaires. It has a lightweight steel housing and is based on backlight, yet it is only 35 mm height. High quality non-yellowing PMMA micro prismatic front optics. Easy tool-free installation, twist connector between driver and panel and junction box with automatic strain relief for cables or plastic tubing.

Sense Basic 300x600



Produkt- og miljøbilleder



Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 7021982121463 Sense Basic 300x600 Hvid 2180lm 3000K Ra>80 On/Off 20W LED 109 lm/W SDCM:3 L80/B20>100.000 Direkte, Opalprismatisk	Klasse II IP20 IK06	On/Off	Indoor 3 pol Linect / klemmerække	L595 x W295 x H36 x D36
 7021982121470 Sense Basic 300x600 Hvid 2220lm 4000K Ra>80 On/Off 20W LED 111 lm/W SDCM:3 L80/B20>100.000 Direkte, Opalprismatisk	Klasse II IP20 IK06	On/Off	Indoor 3 pol Linect / klemmerække	L595 x W295 x H36 x D36
Tilbehør				
 5703821177344 Nødlysboks Driver DALI / EM Selvtest, DALI Nødlys 3 timer	L270 x W75 x H35			
 5703821177276 Nødlysboks On-Off/Bagkantsdæmp / EM Selvtest, Nødlys 3 timer	L270 x W75 x H35			
 5703821177504 Nødlysboks Driver DALI / EM DALI/Selvtest, Nødlys 3 timer	L270 x W75 x H35			