












StripLine is a flexible LED strip system designed to provide architectural lighting on ceilings and walls, in niches and cabinets, and is suitable for both indoor and outdoor use. StripLine RGBW allows you to create all the colours of the rainbow by mixing red, green and blue (RGB) in different ways. It also features pure white (W). StripLine RGBW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch. The LED strip is encapsulated to an IP54 rating, and is supplied with mounting tape on the rear and connection cables already fully fitted. The LED strip must be fitted in one of the available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. (The diffuser on roll and the Round Diffuser are not compatible with the Slim and Soft profiles). Different driver kits are available, dimmable with phase-cut or push dim. Driver kits come complete with screwless terminal block for looping. The drivers are encapsulated to an IP20 rating. StripLine RGBW can be cut at intervals of 7.1 cm to be tailored to each individual installation. When cutting, silicone should be applied to maintain water protection.

StripLine RGBW



Produkt- og miljøbilleder



Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 <p>7021983914521 StripLine 5m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50.000 Beam: 120°, Direkte,</p>	Klasse III IP54		Påbygget, Indoor / Outdoor Kabel 2x2m	L5000 x W12 x H3.2
 <p>7021983914798 StripLine 10m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50.000 Beam: 120°, Direkte,</p>	Klasse III IP54		Påbygget, Indoor / Outdoor Kabel 2x2m	L10000 x W12 x H3.2
Driver				
 <p>7021988204443 IP65 Koblingsboks Sort Med driver 90W Bagkantsdæmp</p>				L346 x W127 x H53
 <p>7021988204405 SG Hvid Driver 24V 36W Bagkantsdæmp</p>				L200 x W85 x H35
 <p>7021988204412 SG Hvid Driver 24V 75W Bagkantsdæmp</p>				L200 x W85 x H35
 <p>7021988204429 SG Hvid Driver 24V 150W Bagkantsdæmp</p>				L310 x W85 x H35
Tilbehør				
 <p>7021983914576 Remote Control Sort RF RGBW</p>				L139 x W36 x H11
 <p>7021983914552 Controller Hvid RF RGBW Fjernkontroll RF / Push Dim</p>				L175 x W45 x H27
 <p>7021988204832 LEDDim Smart Color Controller Hvid SG Smart/ Fjernkontroll RF * / Push Dim</p>				L175 x W45 x H27