

Tysnes 66 Pro



Tysnes 66 Pro is a very efficient, robust version in the Tysnes 66 family. With very high light output and long lifetime it is the project winner for storage rooms, garages, and parking facilities. The luminaire is produced from impact-resistant UV stabilized polycarbonate, and the components can withstand vibrations and very low temperatures (-40°C). It can easily be mounted on ceilings with clips or suspended in wires. Sturdy steel clips attached to the luminaire holds the diffuser. It has cable entries in both ends and weakening for cabling from the back. 5-pole (On/Off) or 7-pole (DALI) terminal block with 5 x 2,5 mm² through wiring gives flexibility for larger installations.

Tysnes 66 Pro



Produkt- og miljøbilleder



Artikel	Beskyttelse	Styring	Montering/Tilslutning	Dimensioner
 7021981200534 Tysnes 66 Pro 1500 Grå 9430lm 4000K Ra>80 DALI-2 55W LED 171 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 119°, Direkte, Opal	Klasse I IP66 IK10	DALI-2	Påbygget, Indoor Klemmerække	L1500 x W85 x H80
 7021981200510 Tysnes 66 Pro 1500 Grå 9430lm 4000K Ra>80 On/Off 55W LED 171 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 119°, Direkte, Opal	Klasse I IP66 IK10	On/Off	Påbygget, Indoor Klemmerække	L1500 x W85 x H80
 7021981200626 Tysnes 66 Pro 1500 Grå 11060lm 6500K Ra>80 On/Off 69W LED 160 lm/W SDCM:3 L90/B10>100.000, L90>50.000 Beam: 114°, Direkte, Opal	Klasse I IP66 IK10	On/Off	Påbygget, Indoor 5-polet klemrække med 5 x 2,5 mm ² gennemfortrådning	L1500 x W85 x H80
Tilbehør				
 7021981200633 Tysnes 66 45° Fæste				L45 x W43 x H43
 5703821177559 Wiresæt 2x5m				L19 x W25 x H150
 5703821177566 Montagesæt for justerbar vinkling				L100 x W98 x H95