

LEDDim 400



Dimmer for mounting in wall box (EU) Setting of minimum level, 3–400 VA load, input for push dim functionality. Five-year system warranty for dimmer when it is used together with SG products.

LEDDim 400



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
LEDDim				
 820330 LEDDim Grey Plastic			Indoor	L56 x W5 x H56
 820410 LEDDim White 400VA	IP20	Trailing edge dimming	Recessed, Indoor	L84 x W84 x H42
 820411 LEDDim 2-pole White 400VA	IP20	Trailing edge dimming	Recessed, Indoor	L84 x W84 x H42
Accessories				
 820352 LEDDim 350/400/Smart White ABB Adapter Polycarbonat (PC)				L55 x W55 x H10
 820353 LEDDim 350/400/Smart White Schneider Adapter Polycarbonat (PC)				L56 x W56 x H12
 820417 LEDDim 350/400/Smart Black SG Front Polycarbonat (PC)				L83 x W83 x H29
 820418 LEDDim 350/400/Smart Silver Elko Adapter ABS				L55 x W55 x H12
 820424 LEDDim 350/400/Smart White SG Front Polycarbonat (PC)				L83 x W83 x H23