

CE – Declaration of Conformity

Document: CE-UKCA250203B_DiLED IV Linear
 Product Inspection: PI250122A
 Risk Assessment: RA250113C

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

DiLED IV Linear

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

<i>Directive 2014 / 30 / EU</i>	<i>Directive 2014 / 35 / EU</i>	<i>Directive 2009 / 125 / EF</i>
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	(Regs 244/2009, 245/2009, 347/2010)* Ecodesign requirements (ECO) * As applicable and including amendments

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires – emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)

CE declaration date: 2025

Statement of Conformity

issued by SG Armaturen AS

Manufacturer

Lillesand, 03/02-2025
 Place and date of issue

Martin Ettrup

Approval Engineer
 Name of authorized person


 Signature of authorized person

UKCA – Declaration of Conformity

Document: CE-UKCA250203B_DiLED IV Linear
 Product Inspection: PI250122A
 Risk Assessment: RA250113C

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

DiLED IV Linear

Name(s)

To which this declaration relates is in conformity with the following UK-regulations:

<i>UK SI 2016 No. 1091</i>	<i>UK SI 2016 No. 1101</i>	<i>UK SI 2010 No. 2617</i>	<i>UK SI 2012 No. 3032</i>
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires – emergency lighting)
EN 62722-1:2022	(Luminaire performance - General requirements)
EN 62722-2-1:2023	(Luminaire performance - Particular requirements)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)
UK SI 2021 No. 1095	(Luminaires – The Ecodesign for Energy-Related products and Energy Information)

UKCA declaration date: 2025

Statement of Conformity

issued by SG Armaturen AS

Manufacturer
Lillesand, 03/02-2025
 Place and date of issue

Martin Ettrup
Approval Engineer
 Name of authorized person


Signature of authorized person

Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
5703821179362	DiLED IV 297x1194 White 3830lm	4000K Ra>80 DALI-2	130268
5703821179379	DiLED IV 297x1194 3830lm	4000K Ra>80 On/Off	130268
5703821179393	DiLED IV 300x1200 White 3830lm	4000K Ra>80 On/Off	130268
5703821179386	DiLED IV 300x1200 White 3830lm	4000K Ra>80 DALI-2	130268
5703821182997	DiLED IV 745x1205 Silver 4450lm	4000K Ra>80 DALI-2	130268
5703821182898	DiLED IV 297x1394 White 3780lm	4000K Ra>80 DALI-2	130268
5703821182904	DiLED IV 297x1794 White 5660lm	4000K DALI-2	130268
5703821182874	DiLED IV 297x1194 White 4000lm	4000K DALI-2	130268
5703821182935	DiLED IV 300x1349 White 2550lm	4000K Ra>80 CD-DALI 3H EM PRO DALI	130268
5703821182928	DiLED IV 300x1349 White 2550lm	4000K Ra>80 DALI-2	130268
5703821182881	DiLED IV 297x1194 White 4000lm	4000K Ra>80 DALI Emergency 3H	130268
5703821182911	DiLED IV 299x899 White 2900lm	4000K Ra>80 DALI-2	130268
5703821179164	DiLED IV 370x1790 White 3500lm	4000K Ra>80 DALI-2	130268
5703821181501	DiLED Iv 300x1200 White 4000lm	4000K Ra>80 DALI-2	130268

Emergencybox

5703821177276	Emergencybox	On-Off/Trailing edge / EM Self test, Emergency 3h	130268
5703821177344	Emergencybox Driver	DALI / EM Self test, DALI Emergency 3H	130268
5703821177504	Emergencybox Driver	DALI / EM DALI/Self test, Emergency 3 hours	130268