

Wave 900 White 4000lm 3000K Ra>80 On/Off

Article code: 111270
EAN: 7021981112707



Electrical

System wattage: 31W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 14, B16: 23, C10: 22, C16: 36
Leakage current (mA): 0.31

Light technic

Type of light source: LED
Luminous flux: 4000lm
Efficacy: 129 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B10>100,000
Lifetime: L80/B10>70,000
Light distribution: Direct
Optic: Opal
Beam angle: 110°
UGR: UGR<25
Photobiological safety: RG 0

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IK Class: IK06
IP Class: IP44

Energy and approvals

Contains light source of energy class: C/D
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
Sunda Hus: C-

Materials and finish

Housing: Steel, Aluminium
Colour: White (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Indoor
Module: 900
Connection: 5-pole screwless terminal block with 5x2,5mm² coupling from center to end

Dimensions

Length (mm) L: 920
Width (mm) W: 151
Height (mm) H: 54
Weight (kg) gross/net: 2.64 / 2.121

Packaging

Packing dimensions (mm): 930 x 160 x 60

