

Wave 900 White 4000lm 3000K Ra>80 Sensor Wireless

Article code: 111272
 EAN: 7021981112721

• = This article is produced by order, with an expected delivery time of 3-4 weeks.


Electrical

System wattage: 31W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 14, B16: 23, C10: 22, C16: 36

Light technic

Type of light source: LED
 Luminous flux: 4000lm
 Efficacy: 129 lm/W
 Colour temperature: 3000K
 Colour rendering (Ra): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B10>100,000
 Lifetime: L80/B10>70,000
 Light distribution: Direct
 Optic: Opal
 Beam angle: 110°
 UGR: UGR<25
 Photobiological safety: RG 0

Control/Dimming

Type: Sensor Wireless

Protection

Luminaire class: Class I
 IK Class: IK06
 IP Class: IP44

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Steel, Aluminium
 Colour: White (RAL 9003)
 Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Indoor
 Module: 900
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 920
 Width (mm) W: 151
 Height (mm) H: 54
 Weight (kg) gross/net: 2.88 / 2.121

Packaging

Packing dimensions (mm): 930 x 160 x 60

