

Article code: 111275
EAN: 7021981112752
Replaces: 11265



System wattage: 18W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Type of light source:	LED
Luminous flux:	2140lm
Efficacy:	119 lm/W
Colour temperature:	3000K
Colour rendering (Ra):	Ra>80
MacAdams factor:	SDCM: 3
Lifetime:	L70/B50>50,000
Light distribution:	Direct
Optic:	Opal
Beam angle:	110°
UGR:	UGR<25
Photobiological safety:	RG 0

Luminaire class:	Class I
IK Class:	IK06
IP Class:	IP44

Contains light source of energy class:	D
Breem:	Fulfil Hea 01 for flicker free lighting
BVB:	Yes
Sunda Hus:	C+

Housing:	Steel, Aluminium
Colour:	White (RAL 9003)
Optics:	Acrylic (PMMA)

Mounting: Surface, Indoor
Module: 600
Connection: 4-pole screwless terminal block with 4x2,5mm²
coupling from center to end

Length (mm) L:	620
Width (mm) W:	151
Height (mm) H:	54
Weight (kg) gross/net:	2.244 / 1.77

Packing dimensions (mm): 640 x 160 x 60

