

Wave 600 White 2330lm 4000K Ra>80 DALI-2

Article code: 111289
 EAN: 7021981112899



• = This article is produced by order, with an expected delivery time of 3-4 weeks.

**Electrical**

System wattage: 18W
 Voltage: 220-240V

Light technic

Type of light source: LED
 Luminous flux: 2330lm
 Efficacy: 129 lm/W
 Colour temperature: 4000K
 Colour rendering (Ra): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B50>50,000
 Light distribution: Direct
 Optic: Opal
 Beam angle: 110°
 Photobiological safety: RG 0

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class I
 IK Class: IK05
 IP Class: IP44

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Steel, Aluminium
 Colour: White (RAL 9003)
 Optics: Acrylic (PMMA)

Mounting/Connection


Mounting: Surface, Indoor
 Module: 600
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 620
 Width (mm) W: 151
 Height (mm) H: 54
 Weight (kg) gross/net: 2.244 / 1.77

Packaging

Packing dimensions (mm): 640 x 160 x 60



7 0 2 1 9 8 1 1 2 8 9 9