

Prelude Square



Prelude Square 1200 White 2700lm 2700K Ra>90 Trailing edge

Article code: 111410
EAN: 7021981114107



Electrical

System wattage: 22W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 2700lm
Efficacy: 123 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L90/B10>
Lifetime: L80/B10>100,000
Light distribution: Direct
Optic: Acrylic diffuser
UGR: UGR<28

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK05
IP Class: IP44 (mounted horizontally) / IP40 (mounted vertically)

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Surface, Indoor
Module: 1200
Connection: Screwless terminal block

Dimensions

Width (mm) W: 1196
Height (mm) H: 60
Depth (D): 52
Weight (kg) gross/net: 1.99 / 1.745

Packaging

Packing dimensions (mm): 1205 x 65 x 65



7 0 2 1 9 8 1 1 4 1 0 7