

CE IP66 IK10 EL D

System wattage:	36W
Voltage:	220-240V
Max. luminaires per circuit breaker:	B10: 12, B16: 19, C10: 20, C16: 32
Leakage current (mA):	0.27

Type of light source:	LED
Luminous flux:	4500lm
Efficacy:	125 lm/W
Colour temperature:	4000K
Colour rendering (Ra):	Ra>80
MacAdams factor:	SDCM: 3
Lifetime:	L80/B10>100,000
Lifetime:	L90/B50>50,000
Minimum ambient temperature:	-25°C
Maximum ambient temperature:	45°C
Lifetime at max ambient temperature:	L80/B20>50,000
Light distribution:	Direct
Optic:	Opal
Beam angle:	100°
UGR:	UGR<28

Type: On/Off

Luminaire class:	Class I
IK Class:	IK10
IP Class:	IP66
Fire protection class:	850°C - 30s

Contains light source of energy class:	D
Breem:	Fulfils Hea 01 for flicker free lighting
BVB:	Yes
Sunda Hus:	C+
Food Safety approved (IFS and HACCP):	Yes

Housing:	UV-stabilized polycarbonate
Colour:	Grey
Optics:	UV-stabilized polycarbonate

Mounting: Surface, Indoor
Connection: 5-pole screwless terminal block with 5x2,5mm² through wiring

Length (mm) L:	1174
Width (mm) W:	92
Height (mm) H:	70
Weight (kg) gross/net:	2.832 / 2.36

Packing dimensions (mm):	1230 x 110 x 80
--------------------------	-----------------

