

Area 66



Area 66 Grey 5930lm 4000K Ra>80 DALI-2

Article code: 120004
EAN: 7021981200046



Electrical

System wattage: 46W
Max. luminaires per circuit breaker: B10: 15, B16: 24, C10: 24, C16: 38
Leakage current (mA): 0.30

Light technic

Type of light source: LED
Luminous flux: 5930lm
Efficacy: 129 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>100,000
Lifetime: L90/B50>50,000
Minimum ambient temperature: -25°C
Light distribution: Direct
Optic: Opal
Beam angle: 100°
UGR: UGR<28

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP66

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: UV-stabilized polycarbonate
Colour: Grey
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor
Connection: 7-pole screwless terminal block with 5x2,5mm2 (+DALI) through wiring

Dimensions

Length (mm) L: 1460
Width (mm) W: 92
Height (mm) H: 70
Weight (kg) gross/net: 2.904 / 2.42

Packaging

Packing dimensions (mm): 1515 x 110 x 80



7 0 2 1 9 8 1 2 0 0 0 4 6